

Ultrastar™ A7K2000

3.5-INCH ENTERPRISE HARD DISK DRIVES

HITACHI
Inspire the Next

Shipping the world's first enterprise class, 7200 RPM, 2TB drive for high-capacity nearline environments

Highlights

- > Up to 2 terabytes¹ of capacity
- > Enhanced Rotational Vibration Safeguard (RVS) for robust performance in multi-drive environments
- > 24x7 enterprise-class duty cycle
- > Targeted 1.2 million hours MTBF²
- > 5-year warranty
- > 3Gb/s SATA for configuration flexibility

Applications

- > Data warehousing & mining
- > Disk-to-disk backup & archiving
- > Rack mounted RAID arrays
- > Network Attached Storage (NAS)
- > Cloud storage
- > Massive Scale Out (MSO)



2TB, 1TB, and 500GB
7200 RPM | SATA 3Gb/s



Doubling the capacity density

As data center professionals across the globe work to meet growing enterprise needs, they face the dilemma of storing more data in the same footprint while also reducing power and HVAC consumption. The new Ultrastar™ A7K2000 provides twice the data storage capacity of the prior generation Ultrastar A7K1000 drive, and does so using fewer watts. It is now possible to achieve a colossal 1.2 petabytes (PB) in the footprint of a standard 19-inch enterprise storage rack by deploying the 2TB A7K2000 in a stack of ten 4U, 60-bay enclosures.

Combining 7200 RPM performance and granular power control

Operating at 7200 RPM, the Hitachi Ultrastar A7K2000 offers better overall performance than slower-RPM, capacity-oriented drives at impressively low power-consumption rates. When compared to the previous generation Ultrastar A7K1000, the A7K2000 offers up to a 155% improvement in sustained data transfer rate, and a 120% improvement in watts-per-GB. With five Advanced Power Management modes, a 36% reduction in watts during low-RPM idle mode, and using less than 1W during standby/sleep mode, the Ultrastar A7K2000 can help data centers achieve lower AC power and HVAC requirements, freeing up precious headroom for growing enterprise needs.

Enhancing data safety and security

To ensure the utmost in data safety and security, the Ultrastar A7K2000 is also available with a bulk data encryption (BDE) option. When enabled, the Hitachi BDE implementation encrypts all data on the drive using a private security key as it is written to the disk, and then decrypts it with the key as it is retrieved, giving users an extreme level of data protection. Unlike software-based encryption solutions, the Hitachi BDE implementation is hardware-based, so it doesn't slow the system down. This technology also speeds up and simplifies the drive re-deployment and decommissioning process. By deleting the encryption key, the data is rendered unreadable, thereby eliminating the need for time-consuming, multi-pattern data overwrite.

Delivering industry-leading reliability

With a robust fourth-generation mechanical design, Ultrastar A7K2000 is specifically built and tested for the enterprise. The Ultrastar SATA drive family features Hitachi-patented Rotational Vibration Safeguard (RVS) sensor technology, which optimizes drive reliability in multi-drive RAID arrays and rack-mounted systems. Backed by a five-year warranty, the Ultrastar platform has earned Hitachi a reputation among server and storage vendors as a global partner dedicated to delivering the highest quality and reliability in the industry.

Innovation for a more sustainable environment

The Ultrastar A7K2000 demonstrates Hitachi ecological leadership with its halogen-free design and power-efficient operation. Both these features serve to qualify the drive for the Hitachi EcoTrac classification, which identifies products that minimize environmental impact in the areas of product design, manufacturing, operation and disposal.

Specifications

Model(s)	Standard models	BDE models
	HUA722020ALA330 HUA722010CLA330 HUA722050CLA330	HUA722020ALA331 HUA722010CLA331 HUA722050CLA331
Configuration		
Interface	SATA 3Gb/s	
Capacity (GB) ¹	2TB / 1TB / 500	
Sector size (bytes)	512	
Max. areal density (Gbits/sq. in.)	2TB <2TB	285 352
Performance		
Data buffer (MB) ³	32	
Rotational speed (RPM)	7200	
Interface transfer rate (MB/s, max)	300	
Sustained transfer rate (typical, MB/sec)	134	
Seek time (read, typical, ms) ⁴	2TB <2TB	8.2 8.5
Reliability		
Error rate (non-recoverable, bits read)	1 in 10 ¹⁵	
Load/unload cycles (at 40° C)	300,000	
Availability ² (hrs/day x days/wk)	24x7	
Targeted MTBF ² (hrs)	1,200,000	
Warranty (yrs)	5	
Acoustics		
Idle (typical, Bels)	2TB <2TB	2.9 2.4
Power		
Requirement	+5 VDC (+/-5%), +12 VDC (+10%/-8%)	
Startup current (max. A)	2.0 (+12V), 1.2 (+5V)	
Read/write (W)	2TB <2TB	11.1 8.4
Unload Idle (W)	2TB <2TB	5.6 3.9
Power consump. efficiency index (W/GB)	0.0028 / 0.0039 / 0.0078	
Physical size		
z-height (mm)	26.1	
Dimensions (width x depth, mm)	101.6 (+/-0.25) x 147	
Weight (typical, g, max.)	2TB <2TB	740 680
Environmental (operating)		
Ambient temperature	5° to 60° C	
Shock (half-sine wave, G)	70	
Vibration, random (G RMS 5 to 500 Hz)	0.67 (XYZ)	
Environmental (non-operating)		
Ambient temperature	-40° to 70° C	
Shock (half-sine wave, G)	2TB <2TB	300 350

¹ One GB is equal to one billion bytes and one TB equals 1,000 GB (one trillion bytes) when referring to hard drive capacity. Accessible capacity may be less.
² Intended for use in lower duty cycle environments in the enterprise storage hierarchy, such as RAID and nearline applications. This MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under nominal operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.
³ Portion of buffer capacity used for firmware
⁴ Excludes command overhead

Hitachi Global Storage Technologies trademarks are intended and authorized for use only in countries and jurisdictions in which Hitachi Global Storage Technologies has obtained the rights to use, market and advertise the brand. Contact Hitachi Global Storage Technologies for additional information. Hitachi Global Storage Technologies shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks.

References in this publication to Hitachi Global Storage Technologies' products, programs or services do not imply that Hitachi Global Storage Technologies intends to make these available in all countries in which it operates.

Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary. Please visit the Support section of our website, www.hitachigst.com/support, for additional information on product specifications. Photographs may show design models.

Hitachi quality and service

Hitachi's Ultrastar A7K2000 extends the company's long-standing tradition of performance and capacity leadership. The proven drive design enables high reliability and availability to customer data. Ultrastar quality, performance, and world class technical support and service provides customers with a lower total cost of ownership over previous generations.

Hitachi drives are backed by an array of technical support and services, which may include customer and integration assistance. Hitachi is dedicated to providing a breadth of hard disk drive solutions to satisfy all of today's demanding computing needs.

How to read the Ultrastar model number

HUA722020ALA330 = 2TB, 32MB buffer

H = Hitachi

U = Ultrastar

A = Series prefix

72 = 7200 RPM

20 = Full capacity—2TB

20 = Capacity this model, 20 = 2TB

(10 = 1TB, 50 = 500GB)

A = Generation code

L = 26.1mm z-height

A3 = Interface, SATA 3Gb/s

3 = 32MB buffer

0 = No BDE (1 = BDE)

Information and Technical Support

www.hitachigst.com (Main Web site)

www.hitachigst.com/partners (Partner Web site)

North America

support_usa@hitachigst.com

Toll free: 1 888 426-5214, Direct: 1 507 322-2370

Asia Pacific

support_ap@hitachigst.com / 65 6840 9595

EMEA and UK

support_uk@hitachigst.com / 44 20 7133 0032

Germany

support_uk@hitachigst.com / 49 6929 993601

Program Support

Partners First™ Program

channelpartners@hitachigst.com

© 2009 Hitachi Global Storage Technologies

Hitachi Global Storage Technologies
3403 Yerba Buena Road
San Jose, CA 95135 USA

Produced in the United States 8/09. All rights reserved.

Ultrastar™ and Partners First™ are trademarks of Hitachi Global Storage Technologies.

The EcoTrac symbol identifies Hitachi hard drives that deliver on the principles of lower operating costs, safer product disposal and a more sustainable environment.

 **Hitachi Global Storage Technologies**