

VDS - NVR50 1HE / INDUSTRY

up to 60 cameras



System	
CPU	Intel® Core™ i3-10100TE Prozessor
Chipsatz	Intel® W480E chipset
Main Memory	16 GB DDR4 3200 RAM, Up to 128 GB RAM
GPU	Intel® UHD-Grafik 630
Display	1x HDMI, 1x DP
Ethernet	4x RJ45 Gigabit Ethernet LAN ports
RAID Support	OS: 0/1 Live data: 0/10 Archive data -
Front I/O Panel	2x USB 3.0
Rear I/O Panel	2x 230V Power in 1x VGA (Resolution up to 1920 x 1200 @ 60 Hz) 1x DVI-D (Resolution up to 1920 x 1200 @ 60 Hz) 1x HDMI 2.0 (Resolution up to 4096 x 2160 @ 60 Hz) 4x LAN 100/1000 (3x I210AT, 1x I219LM) 4x USB 3.2
Storage	
OS	up to 1x 1920 GB NVME or 2x 7,68 TB SSD
Live	up to 4x 18 TB HDD or 4x 7,68 TB SSD
Archive	-
Environmental	
Operating Temperature	0 – 40 °C (Recommended temperature 20 – 22 °C)
Vibration (5 ~ 500 Hz)	[1HE] 0,25 Grms [INDUSTRY] 1Grms / 2 G for internal disks
Shock	10 G (with 11 ms duration, half sine wave)
Power Requirement	
Power Supply	[1 HE] 650W 80 PLUS Hot-swap redundant [INDUSRTY] 500W 80 PLUS GOLD
Mechanical	
Dimension (HxWxD)	[1 HE] 43,9 x 438 x 530 mm [INDUSRTY] 88 x 426,4 x 525 mm