

HPC-7242 + ASMB-587



System	CPU	Intel® Core™ i3-10100(T)E (ECC support) Intel® Core™ i5-10500(T)E Intel® Core™ i7-10700(T)E Intel® Xeon® W-1270E (ECC support)
	Chipsatz	Intel® W480E
	Memory	up to 128GB ECC RAM (4x 32GB)
	Storage	4x 3,5"/2,5" SSD/HDD Front 2x 2,5" SSD/HDD internal 1 x M.2 22110/2280 (PCIe/SATA)
	GPU	Intel® UHD-Grafik 630
	Display	1x VGA, 1x DVI-D, 1x HDMI
	Ethernet	4x RJ45 Gigabit Ethernet LAN
	Front I/O Panel	2x USB 3.0
	Rear I/O Panel	1x / 2x 230V Power in 1x VGA (Resolution up to 1920 x 1200 @ 60 Hz) 1x DVI-D (Resolution up to 1920 x 1200 @ 60 Hz) 1x HDMI 2.0 (Resolution up to 4096 x 2160 @ 60 Hz) 4x LAN 100/1000 (3x I210AT, 1x I219LM) 4x USB 3.2 1x RS232 or IPMI VGA 2x Audio (Mic-in, Line-out)
	PCIe	1x PCIe x16 (Gen3) LP 2x PCIe x4 (Gen3) LP
Environment	Operating Temperature	0 – 40 °C
	Humidity	10 ~ 95% @ 40 °C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms / 2 Grms for internal disks
	Shock	10 G (with 11 ms duration, half sine wave)
	IP	-
Cooling	Chassis Fan	1x (8 cm)
	Air Filter	Yes
Power Supply	Power Supply	500 Watt 80+ Gold 550 Watt 80+ Platinum RPS
Physical Characteristics	Dimension (HxBxT)	[2 HE] 88,4 x 426.4 x 525 mm
OS	Windows	Windows 10/11 Pro / IoT Windows Server 2019/2022
	Linux	Linux 64-bit
Optional		IPMI AST2600 TPM 2.0 Low-Profile rear panel
Available		2030